

DATASHEET EP5



ESS EP5

HIGH VOLTAGE STORAGE BATTERY

From Exelon



The EP5 is a high-performance, scalable battery storage system, allows for maximum flexibility, making it suitable for a broad range of storage applications. Additional batteries can be installed in parallel allowing for a maximum storage capacity of 20.8kwh.



- · 90% Depth of Discharge
- · Floor or Wall Mounting
- · Compact & Easy Installation
- · IP65 Protection Level
- · High Voltage and High Efficiency









Easy Installa⊠on



High Efficiency



Expandable System



DoD

www.exeloness.com











SYSTEM NAME	EP5
ELECTRICAL CHARACTERISTICS	
Compatible PCS	All Series of H1, KH, H3, H3-Pro, US
Battery Type	LifePO4 Prismatic Cell
Nominal Energy [kWh]	5.18
Nominal Voltage [V]	192
Operating Voltage [V]	174 ~ 219
Max.Charge/Discharge Current [A]*1	27
Recommend Charge Current [A]	13.5
Peak Discharge Current [A]	65 @60s
Peak Charge Current [A]	32.4 @5s
Battery Pack Round-Trip Efficiency [%]	≥95
Depth of Discharge [%]	90
Cycle Life	≥4000
Communication	CAN
Display	LED*5
Scalability	Max. 4 Units in Parallel
OPERATING CONDITIONS	11 V H - 7 T I I I I I
Installation Location	Outdoor/Indoor
Operating Temperature [°C]	Charge: 0 ~ 55 Discharge: -10 ~ 55
Storage Temperature [°C]	0~35
Cooling Method	Natural Convection
Humidity [%]	5 ~ 95 (No Condensing)
Altitude [m]	Max. 2,000
MECHANICAL CHARACTERISTICS	INOL
Dimensions (W*H*D) [mm]	380*625*147
Weight [kg]	50.5±2
CERTIFICATES	
Safety	IEC62619
EMC	EN IEC 61000-6-1/3
Transportation	UN38.3
Ingress Protection	IP65

^{*1,} The current is affected by temperature, cell voltage and SOC.